Introducing **Practilite 604** is the most advanced of the Practilite compact LED Fresnel family. Its ideally suited for permanent and semi-permanent installations where compact DMX enabled Fresnel lights can be utilized.

Practilite 604 is the most advanced of the Practilite compact LED Fresnel family. Its ideally suited for permanent and semi-permanent installations where compact DMX enabled Fresnel lights can be utilized. Places like small and home studios for v-logging or even for high quality gallery lighting. Smart Sync Connectivity enables synchronous control from one

The Practilite 604 comes with an app for smartphones and is Bluetooth capable: the remote function is cost-effective and especially useful for single-person shooters or small crews when a gaffer is not available. Also, it makes documentary shooting and field interviews more efficient as managing the lighting setup and adjustments can now be done with

RACTILIT Remote Controllable Bi-Color LED Fresnels

Practilte 604 DMX **Enabled LED Fresnel**



The lights passed the LED refresh rate test with

flying colors. No striping was detectable.

Darran Webb-Lighting Director/Designer

Greater light range

greater ease.

Master fixture.

DMX and Smart Sync Connectivity

The classic fresnel lens provides greater light range than conventional

LED fixtures. This enables wider shot angles and precise light-shaping without losing the LED output power/throw which is typically the case with barndoor-controlled fixtures. This compact and powerful light is designed to gather and throw as much light as possible through its 3.2" 80mm fresnel lens, providing you with unprecedented size to light output ratio.

Variable color temperature

In today"tungsten" anymore. Be it CFL, LED, halogen and other types of lighting, our Practilite 604 is just the right tool to adapt to these various lighting conditions.

SPECIFICATIONS:

Light Source: Dual Phosphor COB LED

Color Range: 3000 to 6000K

CRI: ≤96

Display: OLED screen

Operating Voltage: 100-240 VAC, 50/60 Hz 12-28 VDC

Power Consumption (max): 85W (90 W)

Connectivity: DMX-512

Dimming: 5-100% (0-100% via DMX)

Lens: 3.2" (80 mm), Borosilicate glass Fresnel

Beam Angle: 15-75° Beam Control: Variable

Cooling: Hybrid

Control:

Local

Remotely via Practilite Remote Control App iOS 8.0+ and Android

Mount: 5/8" (Baby) Barndoors: Included

Dimensions: 4.0 x 7.0 x 6.0" (10 x 17 x 15 cm)

Weight: 2.9lbs (1.3kg)



Distributed By:



T: 818.760.8240

Information:chris@maniosdigital.com